

FOG Log

FOR GREASE TRAPS, INTERCEPTORS, AND COLLECTION SYSTEMS

DELIVER CONTINUOUS MAINTENANCE OF GREASE TRAPS, INTERCEPTORS, LIFT STATIONS, WET WELLS, AND COLLECTIONS SYSTEMS AT LESS COST AND EFFORT.

This solid bacterial block breaks down grease, fat, and sludge buildup while reducing strong odors. Utilizing naturally occurring bacteria, each new block is suspended from a rope into the treatment area, where it dissolves gradually over a 30-90 day period. Reduce labor time for dosage maintenance and the need for pump-outs by automating septic and grease trap maintenance with FOG Log.

Use in Wastewater Treatment Systems:

- Lift stations
- Wet wells
- Ponds
- Lagoons
- Basins
- Settling tanks
- Holding tanks
- Digesters

Effective Against:

- Odor
- Grease fats and oils
- Digests waste
- Reduces sludge
- Absorbs phosphates
- Reduces hydrogen sulfide
- Degrades animal slurry systems
- Lowers BOD, TSS, COD, & FOG
- Reduces organic solids & sludge build up
- Reduces filamentous bacteria & associated foam

Features and Benefits:

- Specially formulated to break down yard waste
- Improves settling & percolation
- Improves operational efficiency
- Allows for 24 hour continuous treatment of water, not just periodic dosage
- Greatly reduces labor time needed for dosage maintenance
- Eliminates need for metering pump- no initial or maintenance cost
- Eliminates need for personnel to dose other types of treatments daily or weekly
- Automates waste water system

Directions: Complete directions on product label

Easy to use, simply suspend the block into the treatment area, allowing the block to be placed just away from the higher flow areas. The block will dissolve over a 30-90 day period as the waste water flow washes over it. Higher flows will result in faster degradation of the block

Properties

- Appearance..... Light Red Block
- Fragrance..... No odor
- Colony count..... 4 Billion Colonies/gram
- Bacterial Strains..... 4 strains of Bacillus bacteria
- Storage Stability at 70 °C..... 2 years
- Effective pH Range..... 5.2-9.5
- Effective temperature range. 40-145° F



Packaging/Quantities

- 30 pound block
- 4 x 5 pounds
- 4 x 2 pounds