

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number
Material name Impervious
Revision date January 1, 2015
Supplier information Evcor Solutions Inc.
Toronto Ontario M5V 1T5
Company phone 1-800-860-1537
Emergency telephone US (800) 860-1536
Date January 1, 2015
Product use Protective Coating

2. Hazards Identification

Emergency overview Flammable aerosol. CONTENTS UNDER PRESSURE.
Pressurized container may explode when exposed to heat or flame. Will be easily ignited by heat, spark or flames. May be fatal if inhaled. Cancer hazard. Irritating to eyes and skin.

Prolonged exposure may cause chronic effects.

Potential health effects
Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.
Eyes Contact with eyes may cause irritation.
Skin May cause skin irritation.
Inhalation May cause cancer by inhalation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. May cause irritation of respiratory tract.
Ingestion Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion. Irritating. May cause nausea, stomach pain and vomiting.

Target organs Cardiac. Central nervous system. Kidneys. Liver. Lungs. Respiratory system.
Chronic effects Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Signs and symptoms Symptoms may include redness, edema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Potential environmental effects Components of this product are hazardous to aquatic life. May cause long-term adverse effects in the environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Acetone	67-64-1	15 - 40
Asphalt, oxidized	64742-93-4	10 - 30
Propane	74-98-6	10 - 30
Toluene	108-88-3	10 - 30
Stoddard Solvent	8052-41-3	5 - 10
Magnesium Silicate	14807-96-6	3 - 7
Carbon Black	1333-86-4	1 - 5
Other components below reportable levels		10 - 30

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

In case of shortness of breath, give oxygen. Symptoms may be delayed.

General advice

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Get medical attention if symptoms occur. Show this safety data sheet to the doctor in attendance. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

5. Fire Fighting Measures

Flammable properties

Flammable by WHMIS criteria. Heat may cause the containers to explode. Ruptured cylinders may rocket.

Extinguishing media

Suitable extinguishing media Powder. Alcohol resistant foam. Water. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Specific hazards arising from the chemical Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment for firefighters Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Do not direct water at source of leak or safety devices as icing may occur. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

Cool containers exposed to flames with water until well after the fire is out.

Explosion data

Sensitivity to static discharge Not available.

Sensitivity to mechanical impact Not available.

6. Accidental Release Measures

Personal precautions

Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. If possible, turn leaking containers so that gas escapes rather than liquid. Move the cylinder to a safe and open area if the leak is irreparable. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. Prevent entry into waterways, sewer, basements or confined areas.
Methods for cleaning up	Ventilate the area. Should not be released into the environment. Stop the flow of material, if this is without risk. Isolate area until gas has dispersed. Following product recovery, flush area with water. Clean up in accordance with all applicable regulations. For waste disposal, see section 13 of the MSDS.
Other information	Clean up in accordance with all applicable regulations.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Do not use in areas without adequate ventilation. When using do not eat or drink. Wash thoroughly after handling.
Storage	Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Use care in handling/storage. Store away from incompatible materials (see Section 10 of the MSDS). Level 3 Aerosol.

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH Biological Exposure Indices

Components	Type	Value
Acetone (CAS 67-64-1)	BEI	50 mg/l
Toluene (CAS 108-88-3)	BEI	0.3 mg/g 0.03 mg/l 0.02 mg/l

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	1800 mg/m3 750 ppm	
	TWA	1200 mg/m3 500 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable particles.
Propane (CAS 74-98-6)	TWA	1000 ppm	
Mineral Spirits (CAS 8052-41-3)	TWA	572 mg/m3	
		100 ppm	
Toluene (CAS 108-88-3)	TWA	188 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
		50 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable
Magnesium Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Mineral Spirits (CAS 8052-41-3)	STEL	580 mg/m3	
	TWA	290 mg/m3	
Toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Magnesium Silicate (CAS 14807-96-6)	TWA	2 fibers/ml	
		2 mg/m3	Respirable particles.
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm	
Toluene (CAS 108-88-3)	TWA	20 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	2380 mg/m3	
		1000 ppm	
	TWA	1190 mg/m3	
		500 ppm	
Carbon Black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Magnesium Silicate (CAS 14807-96-6)	TWA	3 mg/m3	Respirable dust.
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
Mineral Spirits (CAS 8052-41-3)	TWA	525 mg/m3	
		100 ppm	
Toluene (CAS 108-88-3)	TWA	188 mg/m3	
		50 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3
		1000 ppm
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m3
		500 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
	TWA	200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Magnesium Silicate (CAS 14807-96-6)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³	Respirable.
		20 millions of particle 2.4 millions of particle	Respirable.

Exposure guidelines**Canada - Alberta OELs: Skin designation**

Toluene (CAS 108-88-3) Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment**Eye / face protection**

Wear safety glasses with side shields (or goggles).

Skin protection

Wear appropriate chemical resistant clothing. Wear protective gloves.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Viscous. Liquid.
Boiling point	160.14 °F (71.19 °C) estimated
Color	Black.
Flash point	-104.44 °F (-75.80 °C) Propellant estimated
Form	Aerosol.
Melting point/Freezing point	Not available.
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Physical state	Gas.
Vapor pressure	40.95 psig @70F estimated
Solubility (water)	Not available.
Specific gravity	0.638 estimated
Flammability limits in air, upper, % by volume	6.5 % estimated
Flammability limits in air, lower, % by volume	1.1 % estimated
Other data	
Heat of combustion	43.74 kJ/g estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.
Hazardous decomposition products	Not available.

Possibility of hazardous reactions

Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

Components
Species

Test Results

Acetone (CAS 67-64-1)

Acute

Dermal

LD50

Rabbit

20000 mg/kg

20 ml/kg

Inhalation

LC50

Rat

76 mg/l, 4 Hours

50.1 mg/l, 8 Hours

Oral

LD50

Mouse

3000 mg/kg

Rabbit

5340 mg/kg

Rat

5800 mg/kg

Other

LD50

Mouse

1297 mg/kg

Rat

5500 mg/kg

Carbon Black (CAS 1333-86-4)

Acute

Oral

LD50

Rat

> 8000 mg/kg

Propane (CAS 74-98-6)

Acute

Inhalation

LC50

Rat

> 1442.847 mg/l, 15 Minutes

658 mg/l/4h

Toluene (CAS 108-88-3)

Acute

Dermal

LD50

Rabbit

12124 mg/kg

14.1 ml/kg

Inhalation

LC50

Mouse

5320 mg/l, 8 Hours

400 mg/l, 24 Hours

Rat

26700 mg/l, If <1L: Consumer Commodity Hours

12200 mg/l, 2 Hours

8000 mg/l, 4 Hours

Oral

LD50

Rat

2.6 g/kg

Other

LD50

Mouse

59 mg/kg

Rat

1332 mg/kg

* Estimates for product may be based on additional component data not shown.

Local effects

Very toxic by inhalation.

Chronic effects

Hazardous by WHMIS criteria. Prolonged exposure may cause chronic effects.

Product name: IMPERVIOUS

Revision date: January 1, 2015 Issue date: January 1, 2015

MSDS CANADA

6 / 9

Carcinogenicity Hazardous by WHMIS criteria. Cancer hazard.

ACGIH Carcinogens

Acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.
Carbon Black (CAS 1333-86-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Magnesium Silicate (CAS 14807-96-6)	A4 Not classifiable as a human carcinogen.
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Asphalt, oxidized (CAS 64742-93-4)	2A Probably carcinogenic to humans.
Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Magnesium Silicate (CAS 14807-96-6)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
	3 Not classifiable as to carcinogenicity to humans.

12. Ecological Information

Ecotoxicological data

Product		Species	Test Results
16 OZ TERAND DURA-COAT RBRIZED COATIN (CAS Mixture)			
Algae	IC50	Algae	291.954 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia	58.4005 mg/L, 48 Hours, estimated
Fish	LC50	Fish	188.5058 mg/L, 96 Hours, estimated
Components			
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Asphalt, oxidized (CAS 64742-93-4)			
Algae	IC50	Algae	56 mg/L, 72 Hours
Toluene (CAS 108-88-3)			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Ecotoxicity Components of this product are hazardous to aquatic life.

Environmental effects Harmful to aquatic organisms. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Persistence and degradability Not available.

Partition coefficient

Acetone	-0.24
Propane	2.36
Stoddard Solvent	3.16 - 7.15
Toluene	2.73

13. Disposal Considerations

Disposal instructions Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Dispose in accordance with all applicable regulations.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information**TDG**

UN number UN1950
UN proper shipping name AEROSOLS, flammable
Hazard class 2.1
Marine pollutant D
Special provisions 80
Packaging exceptions If <1L: Limited Quantity

IATA

UN number UN1950
UN proper shipping name Aerosols, flammable
Transport hazard class(es) 2.1
Labels required 2.1
ERG code 10L
Special precautions for user Read safety instructions, MSDS and emergency procedures before handling.
Packaging Exceptions LTD QTY

IMDG

UN number UN1950
UN proper shipping name AEROSOLS
Transport hazard class(es) 2.1
Labels required None
Special precautions for user Read safety instructions, MSDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.
Packaging Exceptions LTD QTY

IATA; IMDG; TDG**15. Regulatory Information****Canadian regulations**

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS status

Controlled

WHMIS classification

A - Compressed Gas
 B5 - Flammable Aerosols
 D2A - Other Toxic Effects-VERY TOXIC
 D2B - Other Toxic Effects-TOXIC

WHMIS labeling**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This data sheet contains changes from the previous version in section(s):

Product and Company Identification: Product Review
 Toxicological Information: Toxicological Data